

Saddle Clips and Base

TruDesign Saddle Clips and Base are designed for tidy routing of cables, wires, and plumbing hoses.

The Base can either be screwed or glued to a wall or bulkhead providing a 'mounting base' which can be used on its own with a cable-tie for tying down cables and wires or have one of four sizes of Saddle Clips attached to it for supporting various diameters of plumbing hose. For increased security, a cable-tie can be threaded through the Base under and around the Saddle Clip and hose then done up, locking all components together.

If plumbing layouts change in the future, simply remove the hose from the Saddle Clip, then pinch the arms of the Saddle Clip together to unclip and detach it from the Base. A different size of Saddle Clip can then be clicked on to the Base to accept a different diameter of plumbing hose.

Base available in 1 size supporting 4 sizes of Saddle Clips which cover a range of varying hose diameters:



Key Features:

| Feature: | Benefit: |
|---|--|
| Multi-purpose Base. | Can be used on its own to tie down cables & wires or have a Saddle Clip attached for supporting hoses. |
| Dual mounting options for Base – adhesive or screws. | Provides flexibility for mounting to a wall or bulkhead. |
| Click-on Saddle Clips for mounting Hoses on to Base. | No additional fasteners required. Ability to replace Saddle Clip with another size without disturbing Base (if plumbing is changed at some point in future). |
| Dovetail grooves on underside of Base. | Provides undercuts with increased overall surface area for better adhesive performance. No need for fasteners. |
| Durable, flexible Saddle Clip arms. | Accepts hoses of varying outside diameters. |
| Base manufactured from UV stabilised, composite glass- reinforced Nylon 6 (PA6). Saddle Clips manufactured from UV stabilised Acetal copolymer (POM). | High strength, tough and light weight. Can be used in direct sunlight. Will not rust or corrode. Saddle Clip arms are strong yet flexible and will not 'creep' over time under load. |






Part Numbers:

| (Hose min O.D) | Part Number | Description Packaged | Part # Packaged | Bar Code |
|---|-------------|---|-----------------|---------------|
| Saddle Base | 90982 | Saddle Base x 10 | 91070 | 9421007124420 |
| Saddle Clip 13mm (1/2") | 90983 | Saddle Clip x 5 - 13mm (1/2") | 91071 | 9421007124437 |
| Saddle Clip 20mm (¹³ / ₁₆ ") | 90984 | Saddle Clip x 5 - 20mm (¹³ / ₁₆ ") | 91072 | 9421007124444 |
| Saddle Clip 28mm (1 ¹ / ₈ ") | 90985 | Saddle Clip x 5 - 28mm (1 ¹ / ₈ ") | 91073 | 9421007124451 |
| Saddle Clip 38mm (1½") | 90986 | Saddle Clip x 5 - 38mm (1½") | 91074 | 9421007124468 |

Specifications: Saddle Clip Hose OD

| Saddle Clip | 13mm (1⁄2″) | 20mm (¹³ ⁄16″) | 28mm (1 % ″) | 38mm (11⁄2″) |
|------------------|----------------|----------------------------|---------------------|----------------|
| Minimum OD hose: | 13.0mm (0.51") | 20.0mm (0.79") | 28.0mm (1.10") | 38.0mm (1.50″) |
| Maximum OD hose: | 16.0mm (0.63") | 27.0mm (1.06") | 37.0mm (1.46") | 50.0mm (1.97") |

Specifications: Base Dimensions









Installation for Cables & Wires:





- Attach Base to wall, bulkhead, or hull interior using either 2x stainless 8g x ¾ CSK self-tapping screws or by applying a suitable marine-grade adhesive to the underside. If using adhesive, no screws are required the base has undercuts to ensure maximum adhesion area.
 - Some recommended adhesives are 3M[™] Marine Adhesive Sealant 5200, SIKAFLEX[®] 291i Marine Sealant or for fast cure time, Plexus[®] MA310 two-part adhesive.
- To secure wires or cables, thread a cable-tie through the slot on Base and fasten cables tightly.

Installation for Hoses & Pipes:

- After Installation of Base, select a suitable size Saddle Clip for the intended hose and attach to Base by pinching Saddle Clip arms together and pushing onto Base. A 'click' sound indicates attachment.
- Push hose in to Saddle Clip until arms flex outwards and snap over the hose.
- If desired, a cable-tie can be threaded through the slot on the Base and around the Saddle Clip and hose to lock everything in place.
- To disassemble the Saddle Clip from the Base first remove the hose by pulling outward until released from the Saddle Clip. Pinch arms of Saddle Clip together and pull away from the Saddle.



The information contained in this information sheet is for general information purposes only. The information is provided by TruDesign[™] and while we endeavour to keep the information up to date and correct, we make no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability, suitability or availability. Any reliance you place ons uch information is therefore strictly at your own risk.

LEADERS IN MARINE COMPOSITE FITTINGS

